

smart PROX

smartPROX is Proximity based Card Reader. Proximity provides the highest level of convenience and ease usage for access control systems. The technology is cost-effective and it is unaffected by, weather conditions or strong magnetic fields.



Key Features

- Ability to read 26 bit card numbers.
- A Wiegand output that easily interfaces with most existing Wiegand protocol access control panels.
- Compact and Elegant. Easily installed on walls and doors.
- A factory configurable bi-color LED bar and multi-tone buzzer that provides distinguishable indicators.

Benefits:

- Robust and reliable at competitive price
- Compatible with most of existing Access Control Systems
- Indigenous development and manufacturing results in better and faster support
- Audio visual indication of valid or invalid read

Specifications	SPR501
System Features	
Read Range	Upto 8 cms
Data Read	CSN
Type	EM Cards
Transmit Frequency	125 KHZ
Card Read Time	0.1 sec
Output Interface	Wiegand Format (26 bits)
LED Indicator	Bi color LED
Power supply	12 V DC @ 100mA
Dimensions	80W X 83 H X 21 D
Enclosure	ABS Plastic
Color	Black
Cable Specs (Recommended)	5 core, 7/36 shielded cable
Cable Distance from Controller:	80m (Wiegand)

*Specifications and features are subject to change without prior notice.

application areas

- Call center
- Parking
- Club
- Library



308,Puranik Capitol, Opp Hypercity Mall, Kasarvadavli, Ghodbunder Road, Thane West - 400607
Tel.: +91 22 6464 6500
Email: enquiry@smartisystems.com Visit us at: www.smartisystems.com



www.smartisystems.com