

# smartSINGLE NG

The Faster Card based Time and Attendance System  
With a 32 bit Processor



**smartSINGLE NG**, the Card based Time and Attendance System, with a 32 bit processor, is very fast and efficient in all processing and communication functions, faster than any other in its category, making it an ideal option for any organization with a fairly large or very large number of employees as well as for schools. Besides this, it also offers several other advantages in support.

## KEY BENEFITS

- A Stand Alone Single Door Attendance Terminal & Access Control. **smartSINGLE NG** simultaneously provides Access Control as well for a Single Door.
- Most efficient Push Mechanism, for Multi Location Application, to push data from multiple locations to the central location almost in real time.
- Real Time Resource Management through GPRS. With the help of the staff attendance, recorded as early as in the staff bus itself, and reported through GPRS in real time, resources can be organized and managed for the day well in time.
- Attendance and Security for children travelling by school buses. **smartSINGLE NG** records attendance of pupils in the school buses and communicates the same to the mobile DVR in the bus, to forward it to the server in the central location in the school via GPRS
- POE for Minimum Cabling. With Power on Ethernet, there is no need to have a separate power connection.

Many highly prestigious organizations from many sectors such as Banking, Pharma, IT, Mega Retail, Government etc. have been using various Access Control, Time and Attendance and Security related systems of **smart-i** in many of their establishments all over India, for many years.

## Key Highlights

**Added Security for access to the Devices:-** Configurable card verification has been provided for extra security, in addition to the usual login id and password, to access the Controller device.

**Data Security:-** The IP address of the authorized computer/s is mapped with that of the controller, thus making the downloading of the data very secure.

**Enhanced Security Features:-** Anti pass back, facility/establishment code, Time zone, Duress Card/finger for enhanced security.

**Remote and easy Online Up-gradation of the Firmware:-** Device has an inbuilt tri-color LED which indicate various kind of device transaction process i.e.; Access Granted, Unauthorized Access, Command Activated, etc...

**Compact and Elegant Look:-** An aesthetic and elegant design with big LCD and capacitive touch sense keypad is a value addition to the interior of the premises.

## Technical Specification

| Particulars                       | Specifications   |                        |             |                       |
|-----------------------------------|--|------------------------|-------------|-----------------------|
| <b>Model No</b>                   | <b>STNG7030 - TA Series</b><br><b>STNG7030 - AC Series</b> |                        |             |                       |
| <b>Applications</b>               | Time Attendance & Access Control                           |                        |             |                       |
| <b>Hardware Specifications</b>    |  |                        |             |                       |
| <b>CPU</b>                        | 32 Bit RISC ARM Processor                                  |                        |             |                       |
| <b>Memory</b>                     | Up to 8 MB (Flash)   |                        |             |                       |
| <b>Events/Transactions</b>        | Up to 1,00,000   |                        |             |                       |
| <b>No. Users</b>                  | Up to 40,000   |                        |             |                       |
| <b>Operation Modes</b>            | Card Only; Card + PIN<br>(On Wiegand Card Only)            |                        |             |                       |
| <b>Inbuilt Card Reader</b>        | Mifare®; EM cards, HID Iclass & HID Prox                   |                        |             |                       |
| <b>Communications Port</b>        | TCP/IP; Wiegand  |                        |             |                       |
| <b>Controller ID</b>              | Up to 10,000   |                        |             |                       |
| <b>Display</b>                    | 128 X 64 Bicolor COG LCD                                   |                        |             |                       |
| <b>Keypad</b>                     | Capacitive Touch Sense Keypad                              |                        |             |                       |
| <b>LED</b>                        | Tri-color LED Bar  |                        |             |                       |
| <b>Sound</b>                      | Various Beep Sound Indication                              |                        |             |                       |
| <b>Power Supply</b>               | 12 V DC/ 2A (Min) , POE (Optional)                         |                        |             |                       |
| <b>Enclosure</b>                  | ABS Plastic  |                        |             |                       |
| <b>Color</b>                      | Silver & Black   |                        |             |                       |
| <b>Dimension(H x W x D) in mm</b> | 167 x 105 x 45   |                        |             |                       |
| <b>Mounting</b>                   | Wall Mounting  |                        |             |                       |
| <b>Temperature</b>                | 0°C to 50°C  |                        |             |                       |
| <b>Humidity</b>                   | 20% to 90%   |                        |             |                       |
| <b>Access Control Feature</b>     |  |                        |             |                       |
| <b>Applicable in Model Nos</b>    | <b>STNG7030 - AC Series</b>                                |                        |             |                       |
| <b>Facility Code</b>              | Available  |                        |             |                       |
| <b>Time Zone / Access Levels</b>  | 63 + 1 (Free Time Zone) / Unlimited                        |                        |             |                       |
| <b>Time Zone Slots</b>            | 4 slots per Day  |                        |             |                       |
| <b>Anti-Passback</b>              | Hard, Soft, Escort (Reader Wise)                           |                        |             |                       |
| <b>Holiday Settings</b>           | 42   |                        |             |                       |
| <b>Exit switch Supported</b>      | Yes  |                        |             |                       |
| <b>Exit Reader Supported</b>      | Yes  |                        |             |                       |
| <b>Input/Output</b>               | 3 (Door Status, Egress, Fire) / 3 (DOTL, Lock, Alarm)      |                        |             |                       |
| <b>Ordering Information</b>       |  |                        |             |                       |
| <b>Model No</b>                   | <b>Application</b>   | <b>No of Users</b>     | <b>Type</b> | <b>Inbuilt Reader</b> |
| STNG7030-TA-P/S/HP                | Attendance   | 40000                  | Card + Pin  | P - EM Proximity      |
| STNG7030-TA-P/S/HP-POE            | Attendance   | 40000                  | With POE    | S - MIFARE            |
| STNG730-AC-P/S/HP                 | Access   | 40000                  | Card + Pin  | HI - HID iCLASS       |
| STNG7030-AC-P/S/HP                | Access   | 40000                  | Card + Pin  | HP - HID Proximity    |
| <b>Software</b>                   | <b>Application</b>   | <b>Architecture</b>    |             |                       |
| SSA30- AS Series                  | Access (Only)  | Desktop Based Software |             |                       |
| SSTA30- AS Series                 | Attendance (Only)  | Desktop Based Software |             |                       |
| SCMD Pack Series                  | Access + Attendance  | Web-based Software     |             |                       |

## Access Control Solutions



smart-i Designs and Manufactures complete Access Control Solution including Biometric & Card Readers.

\* smart-i Policy is one of constant improvement. We reserve the rights to alter specifications without any prior notice.

smart i ELECTRONICS SYSTEMS PVT. LTD.  
For more information call +91-22-6566 6555 or  
Email us @ enquiry@smartisystems.com  
www.smartisystems.com