

smartFACE series

Model No : SBF2030-S-WIFI-QR-H4

Linux base Aadhar verified Face Biometric Recognition Terminal – with 4.3 inch IPS display



Standalone Face Terminal for Access or Attn.



Dual Core Arm Cortex A7




4.3" IPS HD display screen



Unique live face recognition algorithm



Multiple RFID technologies*



Wiegand In/Out



Wi-Fi Enabled



10M / 100M adaptive Ethernet port



Aadhar Verified Image upload

Main Features:

- Linux based OS
- Lowest face recognition time <0.5 sec for improve speed of operation to control rush
- 2 megapixel dual camera
- 20000 Face Templates & 57000 transactions.
- Face recognition with Alarm warning
- Access restriction to unauthorized person
- Support real time live detection
- 3D noise reduction and FOG passing technology
- Audio-Voice playback in regional language for event
- Dust Proof Device

TECHNICAL SPECIFICATIONS

Brand Name	SBF2030-S-WIFI-QR-H4
Display	4.3 inches IPS HD screen, screen resolution 480*272
Processor	Dual-Core ARM Cortex-A7, @1.0GHz
Operating System	Linux
Sensor	1/2.8" Progressive Scan CMOS
Viewing angle	Vertical viewing angle: 30°; Horizontal viewing angle: 30°
Camera	Dual cameras with 2MP, 1920x1080, 4.5mm lens with QR detection feature
Audio	Voice playback in regional language
Recognition height	1.2~2.2 meters
Recognition distance	0.3~1.5 meters
Recognition time	Less than 0.5 seconds
Storage capacity	57,000 capture records
Face capacity	20,000 pcs
Communications Port	TCP/IP : RJ45 10M / 100M adaptive Ethernet port Wi-Fi : IEEE 802.11b/g/n standard, support 2.4GHz frequency band, speed range 1Mbps-150Mbps (Optional)
Wiegand interface	Wiegand interface input*/output
Input	3 I/P (Door Status, Egress, Fire)
Output	Door Lock
Reader	Mifare Smart Card Reader (13.56Mhz)
Pin	Available
Power	12 V DC/ 2A
Operating Temp	Temp: -30°C - 60°C , & Rh: 0~90%
Size in mm (LXHXW)	88 mm X 160 mm X 17 mm
Mounting	Wall Mounting (*Stand Mounting Optional)
Certification	CE,ROHS

Ordering Information

Model No	Description
SBF2030-S-WIFI-QR-H4	Smart biometric face recognition terminal with Access & Attendance + 2 megapixel dual camera with QR detection + 4.3 inch display + TCP/IP + Wiegand (In*/Out) + Mifare smart Card Reader + WIFI + Touchscreen

Software Compatibility:

BSS-Building Solution Suite web based multi-module software with Employee Self Service

SCMD-AC-100U-smartCOMMANDCONTROL web Based Access Control Management software with Employee Self Service Module

SCMD-DUO-100U (PACK) – smartCOMMANDCONTROL pack web based access + attendance + employee self service software SALM –

smartALARM - Alarm Management Software for smartCOMMANDCONTROL / smartACCESS

SVM20-AS - 'smartVISITOR' Visitor Management Software (Server License) (Advance Edition) with SQL Express database .This will include a common license for Host, Security and Admin .SQL Licence in Customer Scope.

SVM20-ES - 'smartVISITOR' Visitor Management Software (Enterprise Edition) , Web Based Server License (Including Web based Admin & Host module and desktop based security module)-MS SQL Database.

smartTRACK- Mobile attendance Application compatible with android smart phone.

smartUIDAI- Mobile app for Adhar verified image registration


Note: 1) Recommended software with smartFACE series product is SCMD-Duo or BSS

2)*indicate optional

3) Only 1 Access level available, so recommended to use with Access controller for Project where Time zone & Access futures are required


4) Wiegand In only work when not used inbuilt card reader for standalone controller *

smartFACE as a Single Door Access Controller




smartFACE as a Wiegand Reader for Multi-door control

Smart-i or 3rd Party Multidoor controller




**Multi-location
TOPOLOGY**

TOPOLOGY - with STATIC IP




TOPOLOGY - with VPN



Software Key Features

- Multi Location Application
- Bulk Face & Card Activation.
- Integration With Mobile Apps
- Global Access Policy & Default Access Policy
- Integrated HR Module
- Comprehensive Attendance Policy with Leave & Multiple Shift Management.
- Useful MIS Reports For Attendance & Access.
- Integrated Alarm Management
- Integrated Visitor Management

Mechanical Dimensions



Note: Product images are for illustrative purposes only and may differ from the actual product. Some products may have an associated image or photo. These are for reference only and should be considered illustrative. Technical Specifications subject to change without any notice.

Smart-I Electronic Systems Pvt Ltd | Bhumi World Industrial Park | Building No D-7 | Unit No 250 to 253 | Pimpas, Bhiwandi | Thane - 421302, Maharashtra.INDIA

Copyright@Smart-I Electronic Systems Pvt. Ltd. All rights reserved. Technical Specifications, Model Number and Product availability subject to change without notice*.

Connect with us Today - www.smartisystems.com or +91-8767-247-247 | +91- 02522-616500

Email: enquiry@smartisystems.com | sales@smartisystems.com